Zebra DS3678-SR Tragbares Barcodelesegerät 1D/2D LED Schwarz, Grün

Marke : Zebra

Artikel-Code: DS3678-SR0F003VZWW

Produktname : DS3678-SR

DS3678-SR, 1D/2D Imager, 610nm Led, 1280 x 800, One 660nm LED, Bluetooth 4.0 (LE)
Zebra DS3678-SR. Typ: Tragbares Barcodelesegerät, Scanner-Typ: 1D/2D, Sensor-Typ: LED. Übertragungstechnik: Verkabelt & Kabellos, Standard-Schnittstellen: RS-232, USB, Tastaturkeil, Kabellose Reichweite: 100 m. Produktfarbe: Schwarz, Grün, Internationale Schutzart (IP-Code): IP67, Schutzfunktion: Staubresistent, Schockresistent, Wasserfest. Energiequelle: Batterie. Gewicht: 407 g, Breite: 142 mm, Tiefe: 76 mm

Scannen	
Typ *	Tragbares Barcodelesegerät
Optische Sensor-Auflösung	1280 Pixel
Scanner-Typ *	1D/2D
Sensor-Typ *	LED
Lineare (1D) Barcodes unterstützt *	Codabar, Code 11, Code 128, Code 39, Code 93, GS1-128 (UCC/EAN-128), MSI, Plessey, U.P.C.
2D (Matrix & gestapelte) Barcodes unterstützt *	Aztec Code, Verbundstoffcodes, Datenmatrix, Han Xin, MaxiCode, Micro QR Code, MicroPDF417, PDF417, QR Code, TLC-39
Wellenlänge	610 nm
Neigungslesewinkel	-65 - 65°
Steigungslesewinkel	-65 - 65°
Gierlesewinkel	-45 - 45°

Anschlüsse und Schnittstellen	
Übertragungstechnik *	Verkabelt & Kabellos
Standard-Schnittstellen *	RS-232, USB, Tastaturkeil
Kabellose Reichweite	100 m
Bluetooth-Version	4.0
Bluetooth Low Energy (BLE)	✔
Ethernet/LAN	✔

Leistungen	
Internationale Schutzart (IP-Code)	IP67
Schutzfunktion	Staubresistent, Schockresistent, Wasserfest
LED-Anzeigen	✔
Produktfarbe *	Schwarz, Grün

Leistungen	
Programmierfunktionen	✔

Energie	
Energiequelle *	Batterie
Anzahl der Lesen pro Ladung	100000

Gewicht und Abmessungen	
Breite	142 mm
Tiefe	76 mm
Höhe	185 mm
Gewicht *	407 g

Verpackungsdaten	
Mitgelieferte Kabel	USB
Ladestation	✘
Ständer enthalten	✘

Betriebsbedingungen	
Betriebstemperatur	-20 - 50 °C
Temperaturbereich bei Lagerung	-40 - 70 °C
Relative Luftfeuchtigkeit in Betrieb	5 - 95%

Akku/Batterie	
Akku-/Batterietechnologie	Lithium-Ion (Li-Ion)
Akku-/Batteriekapazität	3100 mAh

Technische Details	
Konformitätsbescheinigungen	RoHS

Logistikdaten	
Warentarifnummer (HS)	84716070

5711783323167

8596375045125

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 17-SEP-2026. Prints or copies of Information are only valid on the printed Publication date