# Epson TM-m30III (111): Standard Model, White, EU




**Marke :** Epson

**Artikel-Code:** C31CK50111

**Produktname :** Epson TM-m30III (111): Standard Model, White, EU

- Schickes, brandneues Design: Ultrakompakt, elegant, zuverlässig und erschwinglich
- Verbesserte mobile Konnektivität: Inklusive USB Type-C PD-Tablet-Anschluss mit 18 W Leistung
- Designed für Effizienz: Verfügt über Erkennung des nahen Papierendes und einen überlegenen Abrollmechanismus.
- Entwickelt für raue Umgebungen: IPX2-Schutz vor Flüssigkeiten und antibakterielle Oberflächenbehandlung
- Breitere Plattformunterstützung: Unterstützt jetzt Windows und Android sowie iOS

USB Type-C PD, Wi-Fi, IPX2, Android, Windows, iOS, Weiss

| Drucken | |
|---|---|
| Farbe | ✗ |
| Maximale Auflösung | 203 x 203 DPI |
| Druckgeschwindigkeit (metrisch) | 300 mm/sek |
| Druckgeschwindigkeit (Beleg) | 300 mm/sek |
| Zeichen | Grafik, Barcode, 2D-Strichcode, Text |
| Drucktechnologie * | Thermodruck |
| Typ * | POS-Drucker |

| Papierhandhabung | |
|---|---|
| Unterstützte Papierbreite | 58 - 80 mm |
| Rollenabmessungen | Roll 57mm, Roll 80mm |

| Anschlüsse und Schnittstellen | |
|---|---|
| USB Anschluss * | ✓ |
| Serielle Schnittstelle * | ✓ |
| Übertragungstechnik * | Kabelgebunden |
| Nahfeldkommunikation (NFC) | ✓ |
| Schnittstelle | USB 2.0-A, USB Type-C, Ethernet interface (100 Base-TX / 10 Base-T), Micro SD Card Slot, USB 2.0 Type B (Service Only), Wireless LAN IEEE 802.11a/b/g/n/ac (optional), Drawer kick-out, Wi-Fi Direct (optional), Near Field Communication (NFC) |

| Netzwerk | |
|---|---|
| Ethernet/LAN * | ✓ |
| WLAN * | ✗ |

| Merkmale | |
|---|---|
| integrierte Barcodes * | Code 128 (A/B/C), CODABAR (NW-7), UPC-E, UPC-A, GS1 DataBar, EAN8, GS1-128, EAN13, Code 39, Datenmatrix, Code 93, ITF, MaxiCode, PDF417 |
| Schalldruckpegel (Druck) | 53 dB |
| Mittlere Betriebsdauer zwischen Ausfällen (MTBF) | 360000 h |
| Schneider | ✓ |
| Dauerhaftigkeit des Autoabschneiders | 2,2 Millionen Schnitte |
| Papiersparfunktion | ✓ |
| Tablet laden & synchronisieren | ✓ |
| Lebensdauer des Druckkopfes | 150 km |
| Ursprungsland | Philippinen |

| Betriebsbedingungen | |
|---|---|
| Betriebstemperatur | 5 - 45 °C |
| Temperaturbereich bei Lagerung | -20 - 60 °C |
| Relative Luftfeuchtigkeit in Betrieb | 10 - 90% |
| Luftfeuchtigkeit bei Lagerung | 10 - 90% |

| Systemanforderung | |
|---|---|
| Unterstützt Windows-Betriebssysteme | ✓ |
| Mac-Kompatibilität | ✓ |
| Unterstützte mobile Betriebssysteme | Android, iOS |

| Gewicht und Abmessungen | |
|---|---|
| Breite | 127 mm |
| Tiefe | 127 mm |
| Höhe | 130 mm |
| Gewicht | 1,3 kg |

| Verpackungsdaten | |
|---|---|
| Menge pro Packung | 1 Stück(e) |
| Verpackungsbreite | 210 mm |
| Verpackungstiefe | 240 mm |
| Verpackungshöhe | 210 mm |
| Paketgewicht | 2,36 kg |

| Logistikdaten | |
|---|---|
| Produkte pro Palette | 112 Stück(e) |
| Produkte pro Palettenlage | 14 Stück(e) |
| Anzahl pro Palette (UK) | 160 Stück(e) |
| Produkte pro Palettenlage (UK) | 20 Stück(e) |

| Technische Details | |
|---|---|
| Seitenbeschreibungssprachen | ANK, Traditional Chinese, Simplified Chinese |
| Papiergröße Rollenpapier | 79.50 ± 0.50 (W) mm x dia 83.00 mm, 57.50 ± 0.50 (W) mm x dia 83.00 mm |
| Druck-Geschwindigkeit | Max. 300 mm/sec at 203 x 203 DPI ( printing width80 mm) |
| Technologie | Thermal Line |
| Spannung | 24 V |
| Konformitätsbescheinigungen | CE |
| Stromverbauch | Mean:0.1 A, Mean Receipt unit: approx.1.8 A |

| Merkmale | |
|---|---|
| Montageposition | Horizontal/Vertikal |
| Wandmontage | ✔ |
| Details der eingebauten Sensoren | Roll paper cover open sensor, Paper End Sensor, Paper Near End Sensor, Paper Jam Sensor, Receipt near-end sensor, Receipt paper sensor |

| Design | |
|---|---|
| Produktfarbe * | Weiß |

| Energie | |
|---|---|
| AC Eingangsspannung | 100 - 230 V |
| AC Eingangsfrequenz | 50 - 60 Hz |

| Sonstige Funktionen | |
|---|---|
| Puffergröße | 4 KB |
| Mittelzyklen zwischen Fehler (MCBF) | 65000000 |
| Lebensdauer Druckkopf (Empfangseinheit) | 150 km |

8715946703930

**Catalog Object Cloud**

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 18-SEP-2026. Prints or copies of Information are only valid on the printed Publication date