

Zebra DS2208 Tragbares Barcodelesegerät 1D/2D LED Schwarz

Marke : Zebra

Artikel-Code: DS2208-SR7U2100AZW

Produktname : DS2208

Zebra DS2208. Typ: Tragbares Barcodelesegerät, Scanner-Typ: 1D/2D, Sensor-Typ: LED.
Übertragungstechnik: Kabelgebunden, Standard-Schnittstellen: USB, RS-232, RS-485, Tastaturkeil.
Produktfarbe: Schwarz, Internationale Schutzart (IP-Code): IP42, Zertifizierung: EN 60950-1 2ed + A11 + A1 + A12 + A2:2013, IEC 60950-1 2ed + A1 + A2, UL 60950-1, CAN/CSA-C22.2.... Energiequelle:
Gleichstrom, Netzteil Ausgangsspannung: 5 V, Energieverbrauch: 250 mA. Gewicht: 161,6 g, Breite: 66 mm, Tiefe: 99 mm



Scannen		Leistungen	
Typ *	Tragbares Barcodelesegerät	Zertifizierung	EN 60950-1 2ed + A11 + A1 + A12 + A2:2013, IEC 60950-1 2ed + A1 + A2, UL 60950-1, CAN/CSA-C22.2 No. 60950-1-07 IEC 62471 EN 55022 (Class B); EN 55032 (Class B) EN 55024 EN 61000-3-2 EN 61000-3-3 47 CFR Part 15, Subpart B, Class B ICES-003 Issue 6, Class B
Scanner-Typ *	1D/2D		
Sensor-Typ *	LED		
Lineare (1D) Barcodes unterstützt *	Codabar, Code 11, Code 128, Code 39, Code 93, EAN-13, GS1 DataBar Expanded, Interleaved 2 of 5, MSI, U.P.C.		
2D (Matrix & gestapelte) Barcodes unterstützt *	Aztec Code, Verbundstoffcodes, Datenmatrix, Han Xin, MaxiCode, Micro QR Code, PDF417, TLC-39		
Optische Sensorauflösung (B x H)	640 x 480 Pixel	Energie	
Arbeitsabstand	36,8 cm	Energiequelle *	Gleichstrom
Wellenlänge	645 nm	Netzteil Ausgangsspannung	5 V
Neigungslesewinkel	-65 - 65°	Energieverbrauch	250 mA
Steigungslesewinkel	-65 - 65°	Gewicht und Abmessungen	
Gierlesewinkel	-65 - 65°	Breite	66 mm
Bewegungstoleranz (cm/s)	13	Tiefe	99 mm
Anschlüsse und Schnittstellen		Höhe	165 mm
Übertragungstechnik *	Kabelgebunden	Gewicht *	161,6 g
Standard-Schnittstellen *	USB, RS-232, RS-485, Tastaturkeil	Verpackungsdaten	
Leistungen		Mitgelieferte Kabel	Mikro-USB
Internationale Schutzart (IP-Code)	IP42	Ladestation	✗
LED-Anzeigen	✓	Betriebsbedingungen	
Produktfarbe *	Schwarz	Betriebstemperatur	0 - 50 °C
		Temperaturbereich bei Lagerung	-40 - 70 °C
		Relative Luftfeuchtigkeit in Betrieb	5 - 95%
		Technische Details	
		Konformitätsbescheinigungen	RoHS
		Logistikdaten	
		Warentarifnummer (HS)	84716070



5711783381228



8596375044395



0007198686290

Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.