Zebra DS2208 Tragbares Barcodelesegerät 1D/2D LED Weiß

Marke : Zebra

Artikel-Code: DS2208-SR6U2100AZW

Produktname : DS2208

Zebra DS2208. Typ: Tragbares Barcodelesegerät, Scanner-Typ: 1D/2D, Sensor-Typ: LED. Übertragungstechnik: Kabelgebunden, Standard-Schnittstellen: USB, RS-232, RS-485, Tastaturkeil, Kabellänge: 10 m. Produktfarbe: Weiß, Gehäusematerial: Kunststoff, Internationale Schutzart (IP-Code): IP42. Energiequelle: Gleichstrom, Batteriereichweite: 100 h, Eingangsspannung: 5.5 V. Gewicht: 161,6 g, Breite: 66 mm, Tiefe: 99 mm

Scannen	
Typ *	Tragbares Barcodelesegerät
Scanner-Typ *	1D/2D
Sensor-Typ *	LED
Lineare (1D) Barcodes unterstützt *	Code 11, Code 128, Code 39, Code 93, GS1 DataBar Expanded, U.P.C.
2D (Matrix & gestapelte) Barcodes unterstützt *	Aztec Code, Verbundstoffcodes, Datenmatrix, Han Xin, MaxiCode, Micro QR Code, PDF417, QR Code, TLC-39
Optische Sensorauflösung (B x H)	640 x 480 Pixel
Wellenlänge	645 nm
Steigungslesewinkel	-65 - 65°
Gierlesewinkel	-65 - 65°

Anschlüsse und Schnittstellen	
Übertragungstechnik *	Kabelgebunden
Standard-Schnittstellen *	USB, RS-232, RS-485, Tastaturkeil
Kabellänge	10 m

Leistungen	
Gehäusematerial	Kunststoff
Internationale Schutzart (IP-Code)	IP42
LED-Anzeigen	✔
Produktfarbe *	Weiß

Leistungen	
Zertifizierung	EN 60950-1 2ed + A11 + A1 + A12 + A2:2013, IEC 60950-1 2ed + A1 + A2, UL 60950-1, CAN/CSA-C22.2 No. 60950-1-07 IEC 62471 EN 55022 (Class B); EN 55032 (Class B) EN 55024 EN 61000-3-2 EN 61000-3-3 47 CFR Part 15, Subpart B, Class B ICES-003 Issue 6, Class B

Energie	
Energiequelle *	Gleichstrom
Batteriereichweite	100 h
Eingangsspannung	5.5 V
Energieverbrauch	250 mA

Gewicht und Abmessungen	
Breite	66 mm
Tiefe	99 mm
Höhe	165 mm
Gewicht *	161,6 g

Verpackungsdaten	
Mitgelieferte Kabel	Mikro-USB
Ladestation	✘

Betriebsbedingungen	
Betriebstemperatur	0 - 50 °C
Temperaturbereich bei Lagerung	-40 - 70 °C
Relative Luftfeuchtigkeit in Betrieb	5 - 95%

Akku/Batterie	
Akku-/Batterietechnologie	Lithium-Ion (Li-Ion)
Akku-/Batteriekapazität	2400 mAh

Technische Details	
Konformitätsbescheinigungen	RoHS

Logistikdaten	
Warentarifnummer (HS)	84716070

5711783398486

8596375044364

Catalog Object Cloud

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.

Publication date: 17-SEP-2026. Prints or copies of Information are only valid on the printed Publication date