



## TSC MH641T Etikettendrucker Direkt Wärme/Wärmeübertragung 600 x 600 DPI 152 mm/sek Kabelgebunden Ethernet/LAN

Marke : TSC

Artikel-Code: MH641T-A001-0302

Produktname : MH641T

TSC MH641T. Drucktechnologie: Direkt Wärme/Wärmeübertragung, Maximale Auflösung: 600 x 600 DPI, Druckgeschwindigkeit (metrisch): 152 mm/sek. Übertragungstechnik: Kabelgebunden, Ethernet/LAN, USB Anschluss. Unterstützte Papierbreite: 104 mm. Produktfarbe: Schwarz, Grau

| Drucken                              |                               | Leistungen                           |                                                                                      |
|--------------------------------------|-------------------------------|--------------------------------------|--------------------------------------------------------------------------------------|
| Drucktechnologie *                   | Direkt Wärme/Wärmeübertragung | Zertifizierung                       | FCC Class A, CE Class A, RCM Class A, UL, cUL, TÜV/safety, CCC, KC, BIS, ENERGY STAR |
| Farbe *                              | ✗                             |                                      |                                                                                      |
| Maximale Auflösung *                 | 600 x 600 DPI                 |                                      |                                                                                      |
| Druckgeschwindigkeit (metrisch) *    | 152 mm/sek                    | <b>Design</b>                        | Schwarz, Grau                                                                        |
| Maximum Druckweite *                 | 10,4 cm                       |                                      |                                                                                      |
| Gedrehtes Drucken                    | ✓                             |                                      |                                                                                      |
| <b>Papierhandhabung</b>              |                               |                                      |                                                                                      |
| Breite des Bands                     | 11,4 cm                       |                                      |                                                                                      |
| Farbbandlänge                        | 600 m                         | Display *                            | LCD                                                                                  |
| Medienstärke                         | 0.06 - 0.28 mm                | Bildschirmdiagonale                  | 10,9 cm (4.3")                                                                       |
| Unterstützte Papierbreite            | 104 mm                        | Display-Auflösung                    | 480 x 272 Pixel                                                                      |
| Maximale Medienlänge                 | 2,54 m                        | Farbdisplay                          | ✓                                                                                    |
| Kerndurchmesser                      | 7,62 cm                       | Display-Hintergrundbeleuchtung       | ✓                                                                                    |
| <b>Anschlüsse und Schnittstellen</b> |                               | Steuerung                            | Tasten, Berührung                                                                    |
| Übertragungstechnik *                | Kabelgebunden                 | <b>Energie</b>                       |                                                                                      |
| Ethernet/LAN *                       | ✓                             | AC Eingangsspannung                  | 100-240 V                                                                            |
| USB Anschluss *                      | ✓                             | AC Eingangsfrequenz                  | 50/60 Hz                                                                             |
| Anzahl USB 2.0 Anschlüsse            | 1                             | <b>Betriebsbedingungen</b>           |                                                                                      |
| RS-232 port                          | 1                             | Relative Luftfeuchtigkeit in Betrieb | 25 - 85%                                                                             |
| <b>Leistungen</b>                    |                               | Luftfeuchtigkeit bei Lagerung        | 10 - 90%                                                                             |
| Seitenbeschreibungssprachen          | DPL, EPL, ZPL, ZPL II         | Betriebstemperatur                   | 5 - 40 °C                                                                            |
| Speicherkapazität                    | 256 MB                        | Temperaturbereich bei Lagerung       | -40 - 60 °C                                                                          |
| Flash-Speicher                       | 512 MB                        | <b>Gewicht und Abmessungen</b>       |                                                                                      |
| integrierte Barcodes                 | 1D, 2D                        | Breite                               | 276 mm                                                                               |
| Eingebauter Prozessor                | ✓                             | Tiefe                                | 502 mm                                                                               |
| Anzahl Zeichensatz                   | 8                             | Höhe                                 | 326 mm                                                                               |
|                                      |                               | Gewicht                              | 15,7 kg                                                                              |
|                                      |                               | <b>Lieferumfang</b>                  |                                                                                      |
|                                      |                               | Mitgelieferte Kabel                  | AC, USB                                                                              |



5704174472469

### Catalog Object Cloud



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity. Automated scraping, data mining, or harvesting for the purpose of training machine learning models, neural networks, or artificial intelligence systems is strictly prohibited without a commercial license.