



The HD29A wired barcode reader is made of high-quality materials that ensure durability and has a solid structure, making it ideal for use even in difficult conditions.

It is characterized by an ergonomic shape and balanced weight, **which significantly affects the comfort of everyday use.**

Fast professional barcode scanner HD29A

Model	HD29A		
Light source	650nm Laser	Working temperature	0 to 45 °C
Reading speed	200 scans / second	Storage temperature	-40 to 60 °C
Scan method	automatic/ manual	Operating humidity	5 to 90%
Available interfaces	USB	Storage humidity	5 to 90%
Weight	200 g		
Device dimensions	65 x 165 x 90 mm		
Dimensions with stand	120 x 150 x 240 mm		
Cable length	2000 mm		
Weight with package	350 g		
Dimensions of package	220 x 130 x 90 mm		
Scan confirmation	sound and light signal		
Readable 1D codes	EAN-13, EAN-8, UPC-A, UPC-E, Code 39, Code 93, Code 128, Interleaved 2 z 5, ITF-14, Industrial 2 z 5, Matrix 2 z 5, Codabar, Code 11, MSI/ Plessey, UK/ Plessey, GS1 DataBar, GS1 DataBar Limited, GS1 DataBar Expanded, Telepen, and other one-dimensional		

