Z-Perform[™] 1000T 190 Tag

	Label			Permanent	
Media Type	Labei		Adhesive	Feimanent	
	Receipt		Type	Removable	
	Tag	✓		No Adhesive	✓
	Wristband		Environment	Indoor	✓
Material Type	Paper	✓	Environment	Outdoor	
	Synthetic			Cold Temperature	✓
Printing Technology	Direct Thermal			Deep Freeze	✓
	(no Ribbon Required)		Properties	High Temperature	
	Thermal Transfer (Ribbon Required)	~		Ultra High Temperature	
Finish	Matte	✓		High Tack	
	Gloss			Chemical Resistance	-

Available from stock on ZipShip

Additional Features

- Good print quality when printed with Zebra 2300, 2100, 3400 and 3200 ribbons with a recommended Zebra printer
- BfR Recommendation XXXIV for direct contact with dry, moist and non-fatty foodstuffs
- Complies with DIN EN 71 part 3 and part 9 as the product does not release any heavy metals and does not contain prohibited amines or colourants
- BPA free

Suggested Applications

- Indoor cold temperature labelling
- Visitor identification tags
- Admission tickets
- Warehouse and inventory control tags
- Shop floor / work in progress tracking tickets
- Shelf-edge tags
- Packaging inserts
- Pallet tagging

©2015 ZIH Corp. All rights reserved.



Technical Specifications

	Description		Caliper		
Facestock	Facestock 190gsm matte white uncoated paper			170 microns	
			Total	170 microns ±10%	
Recommended Zebra Printers:		Desktop, mid-range and high-performance thermal printers			
Recommended Zebra Ribbons:		2300, 2100, 3400, 3200			
Minimum Application Temperature: When the label is applied, the environment and surface should be above this temperature		0°C			
Service Temperature Range: Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range		-43°C to 93°C			
Recommended Storage Conditions: Storage of product before use		1 year duration when stored at 0°C to 21°C at 35% to 50% RH			
Expected Life Span in Application: Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated		Indoor use, for 1 year+			

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order from the ZipShip price list or order sample roll SAMPLE5284.